



OCM ANSI ROLLER CHAIN

Chain No. **40** Pitch • 0.500inch / 12.70mm



UNIT Upper:inch
Beneath:mm

OCM Chain No.	ANSI No.	Pitch P	Roller Diam. D	Width between L.P. W	Link Plate		Pin Diam. d	Pin				Trans Pitch E	Average Tensile Strength Lb/kg	Max. Working Load Lb/kg	Approx Weight Lb/ft kg/m
					H	T		L	L1	L2	L3				
OCM40	40	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	0.634 16.1	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	4,300 1,950	860 390	0.443 0.66
OCM40-2	40-2	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	1.202 30.5	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	8,600 3,900	1,455 660	0.874 1.30
OCM40-3	40-3	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	1.773 45.0	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	12,900 5,850	2,139 970	1.304 1.94
OCM40-4	40-4	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	2.340 59.4	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	17,199 7,800	2,822 1,280	10.617 2.59
OCM40-5	40-5	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	2.908 73.8	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	21,499 9,750	3,352 1,520	2.170 3.23
OCM40-6	40-6	0.500 12.70	0.313 7.94	0.313 7.95	0.473 12.0	0.059 1.5	0.156 3.96	3.475 88.2	0.402 10.2	0.319 8.1	0.382 9.7	0.567 14.4	25,799 11,700	3,947 1,790	2.600 3.87

1. Rivetted construction is standard.
Note: Dimensions subject to change. Certified dimensions furnished upon request.

HORSEPOWER RATINGS SINGLE STRAND ROLLER CHAIN

No. of Teeth Small Spkt.	REVOLUTIONS PER MINUTE-SMALL SPROCKET (rpm)																								
	10	25	50	100	200	300	400	500	700	900	1000	1200	1400	1600	1800	2100	2400	2700	3000	3500	4000	5000	6000	7000	8000
11	0.11	0.26	0.49	0.91	1.70	2.45	3.18	3.89	5.26	6.59	6.80	6.80	6.80	5.57	4.67	3.70	3.03	2.54	2.17	1.72	1.41	1.01	0.77	0.61	0.50
12	0.13	0.29	0.54	1.00	1.87	2.70	3.49	4.27	5.78	7.24	7.60	7.60	7.60	6.34	5.32	4.22	3.45	2.89	2.47	1.96	1.60	1.15	0.87	0.69	0.57
13	0.14	0.31	0.59	1.09	2.04	2.94	3.81	4.65	6.30	7.90	8.29	8.29	8.29	7.15	6.00	4.76	3.89	3.26	2.79	2.21	1.81	1.29	0.99	0.78	0.64
14	0.15	0.34	0.63	1.18	2.21	3.18	4.12	5.04	6.82	8.56	8.98	8.98	8.98	7.99	6.70	5.32	4.35	3.65	3.11	2.47	2.02	1.45	1.10	0.87	0.72
15	0.16	0.37	0.68	1.28	2.38	3.43	4.44	5.43	7.35	9.22	9.67	9.67	9.67	8.86	7.43	5.90	4.83	4.04	3.45	2.74	2.24	1.60	1.22	0.97	0.79
16	0.17	0.39	0.73	1.37	2.55	3.68	4.76	5.82	7.88	9.88	10.4	10.4	10.4	9.76	8.19	6.50	5.32	4.46	3.80	3.02	2.47	1.77	1.35	1.07	0.87
17	0.18	0.42	0.78	1.46	2.73	3.93	5.09	6.22	8.42	10.6	11.1	11.1	11.1	10.7	8.97	7.11	5.82	4.88	4.17	3.31	2.71	1.94	1.47	1.17	0.96
18	0.20	0.45	0.83	1.55	2.90	4.18	5.41	6.61	8.95	11.2	11.8	11.8	11.8	11.7	9.77	7.75	6.34	5.32	4.54	3.60	2.95	2.11	1.60	1.27	0
19	0.21	0.47	0.88	1.65	3.07	4.43	5.74	7.01	9.49	11.9	12.6	12.6	12.6	12.6	10.6	8.41	6.88	5.77	4.92	3.91	3.20	2.29	1.74	1.38	0
20	0.22	0.50	0.93	1.74	3.25	4.68	6.06	7.41	10.0	12.6	13.7	13.7	13.7	13.7	11.4	9.08	7.43	6.23	5.32	4.22	3.45	2.47	1.88	1.49	0
21	0.23	0.53	0.98	1.84	3.42	4.93	6.39	7.81	10.6	13.3	14.6	14.8	14.8	14.8	12.3	9.77	7.99	6.70	5.72	4.54	3.72	2.66	2.02	1.60	0
22	0.24	0.55	1.03	1.93	3.60	5.19	6.72	8.21	11.1	13.9	15.3	15.7	15.7	15.7	13.2	10.5	8.57	7.18	6.13	4.87	3.98	2.85	2.17	1.72	0
23	0.25	0.58	1.08	2.02	3.78	5.44	7.05	8.62	11.7	14.6	16.1	16.9	16.9	16.9	14.1	11.2	9.16	7.68	6.56	5.20	4.26	3.05	2.32	1.84	0
24	0.27	0.61	1.14	2.12	3.96	5.70	7.38	9.02	12.2	15.3	16.8	18.0	18.0	18.0	15.0	11.9	9.77	8.19	6.99	5.55	4.54	3.25	2.47	1.96	0
25	0.28	0.64	1.19	2.22	4.13	5.95	7.71	9.43	12.8	16.0	17.6	18.9	18.9	18.9	16.0	12.7	10.4	8.70	7.43	5.90	4.83	3.45	2.63	0	
26	0.29	0.66	1.24	2.31	4.31	6.21	8.05	9.84	13.3	16.7	18.4	19.7	19.7	19.7	17.0	13.5	11.0	9.23	7.88	6.25	5.12	3.66	2.79	0	
28	0.32	0.72	1.34	2.50	4.67	6.73	8.72	10.7	14.4	18.1	19.9	21.5	21.5	21.5	19.0	15.0	12.3	10.3	8.81	6.99	5.72	4.09	3.11	0	
30	0.34	0.77	1.45	2.70	5.03	7.25	9.39	11.5	15.5	19.5	21.4	23.1	23.1	23.1	21.0	16.7	13.7	11.4	9.77	7.75	6.34	4.54	3.45	0	
32	0.36	0.83	1.55	2.89	5.40	7.77	10.1	12.3	16.7	20.9	23.0	24.7	24.7	24.7	23.2	18.4	15.0	12.6	10.8	8.54	6.99	5.00	0		
35	0.40	0.91	1.71	3.19	5.95	8.56	11.1	13.6	18.4	23.0	25.3	27.2	27.2	27.2	26.5	21.0	17.2	14.4	12.3	9.77	7.99	5.72	0		
40	0.46	1.06	1.97	3.68	6.87	9.89	12.8	15.7	21.2	26.6	29.2	32.3	32.3	32.3	32.3	25.7	21.0	17.6	15.0	11.9	9.77	6.99	0		
Lubri- cation	I						II						III												

Remarks) 1. For HP rating of multiple strand, multiply the HP above by multiple strand factor shown in the table at right.
2. The operation in right part of the dotted line is not recommended.
3. The lubrication type is as follows. Type I : Manual & Drip feed, Type II : Oil bath and Disc, Type III : Pump
4. Dimensions & Ratings are subject to change without notice. Certified dimensions furnished upon request.

Number of Strands	2	3	4	5	6
Multiple Strand Factors	1.7	2.5	3.3	3.9	4.6