



S (M) ROLLER

UNIT:mm

e	E	S D	M D	Width between L.P. W	Link Plate		Pin				Weight (kg/m)			
					H	T	d	L	L1	L2	R	F	S	M
2 (1.8)	4 (4.3)	19.05 (15.9)	-	18 (16.1)	22	3.2	7.94	38 (36.4)	18 (17.1)	20 (19.3)	2.5	2.7	2	-
											2.2	2.3	1.8	-
											2	2.1	1.6	-
											1.9	2	1.4	-
2.5	4.5	22.2	-	22.2	32	4.5	11.11	51	24	27	5.6	5.8	5.4	-
											5	5.2	4.8	-
											4.5	4.7	4.3	-
											4.1	4.3	3.9	-
3	5	27	-	25	32	6	12.7	61.5	29	32.5	6.8	7.2	6	-
											6.1	6.5	5.5	-
											5.5	5.8	5	-
											5	5.4	4.5	-
											4.5	4.9	4	-
3.5	6.5	30	31.8	30	38	6.3 *(6.0)	14.29	68	32	36	10	10.2	9.4	9.8
											8.7	8.9	8.1	8.5
											7.5	7.7	6.9	7.2
											6.5	6.7	5.9	6.2
4	8	34.93	38.1	36.5	45	7.9 *(8.0)	15.88	85.5	39.5	46	11.6	12.2	8.4	8.7
											10.4	10.9	7.8	8
5	12	40.08	44.5	50.8	50.8	9.5 *(9.0)	19.05	110.5	51	59.5	19.7	20.7	12	13
											17.2	18.2	11.1	12.2
											15.8	16.6	10.5	11.5
5	10	40	-	45	50.8	9.5 *(9.0)	20.64	103	47.5	55.5	16.8	17.8	-	-
											14.8	15.7	-	-
6	13	44.45	50.8	56.6	63.5	9.5 *(9.0)	22.23	116	54	62	26.2	27.8	14.7	16
											23.4	24.7	13.8	15
											18.7	19.6	12.4	14.5
7	14	50.8	57.2	66	76.2	12.7 *(12.0)	25.4	141	65.5	75.5	45.7	47.6	24	25
											40.4	42	22.9	24
											31.8	33.3	20.2	21
											27.8	29	19	20
8	16.5	57.1	-	76	90	16	32	169	79	90	45.8	48	26.2	-
											39.8	41.8	24.2	-
2.5	4	20.1	-	22.2	25.4	4.8 *(4.5)	9.53	51	24	27	4.3	4.7	3	-
2.3	8.5	22.2	25.4	27	28.6	6.3	11.11	63	30	33	6.7	6.9	4.6	4.9
3.8	6	31.75	34.9	31	38	7.9 *(8.0)	15.88	78.5	37	41.5	10.4	10.7	8.7	9.1
3.5	9	34.93	38.1	36.5	45	7.9 *(8.0)	15.88	86	40	46	12.1	12.4	9.3	9.6
3.8	8	40.08	44.4	36.5	50.8	9.5 *(9.0)	19.05	94	43.5	50.5	17.1	17.6	12.6	13
-	-	22.2	-	27	28.6	6.3 *(6.0)	11.11	63	30	33	-	-	5.6	-
-	-	25	-	28.6	38	6.3 *(6.0)	12.7	66	31	35	-	-	6.5	-
-	-	31.75	-	36.5	38	7.9 *(8.0)	14.29	81.5	39	42.5	-	-	10.3	-