



■ Dimensions

Unit: mm

Coupling No.	Chain Type	Bore Dia. (HD)		AD	TL	BD	BL	S	H	E	F	Coupling Weight (kg/pc)	GD ² × 10 ⁻³ (kgf · m ²)
		Min.	Max.										
CC3012	06B-2	10	16	45	62	26	28.45	5.1	23.7	12	6	0.3	0.2
CC4012	40-2	11	22	61	79.4	36	36	7.4	32.2	16	8	0.8	0.9
CC4014	40-2	11	28	69	79.4	43	36	7.4	32.2	16	8	1.1	1.9
CC4016	50-2	12	32	77	87.4	51.5	40	7.4	32.2	20	4	1.6	3.2
CC5014	50-2	15	35	86	99.7	53	45	9.7	40.6	20	10	2	6.1
CC5016	50-2	15	40	96	99.7	64	45	9.7	40.6	20	10	2.8	9.3
CC5018	50-2	18	45	106	99.7	73.5	45	9.7	40.6	20	10	3.6	14.3
CC6018	60-2	21	56	128	123.5	89	56	11.5	50.2	26	13	6.4	35.9
CC6022	60-2	25	71	152	123.5	114.4	56	11.5	50.2	26	13	9.8	88.8
CC8018	80-2	30	80	170	141.2	115	63	15.2	65.1	28	25	12.8	136
CC8022	80-2	35	100	203	157.2	140	71	15.2	65.1	28	17	19	299
CC10020	100-2	40	110	233	178.8	160	80	18.8	79	34	27	30	594
CC12018	120-2	50	125	255	202.7	170	90	22.7	99.1	32	45	40.5	993
CC12022	120-2	50	140	304	222.7	208	100	22.7	99.1	35	35	65	2,197

■ Case Dimensions

Unit: mm

Coupling No.	Case Outside Dia.	Case Outside Width	Case Weight (kg/pc)	GD ² × 10 ⁻³ (kgf · m ²)	N-M
	OD	CH			
CC3012	60	58	0.1	0.4	4-M4
CC4012	74	70	0.2	1.2	4-M5
CC4014	83	70	0.3	1.8	4-M5
CC4016	90	70	0.3	2.3	4-M5
CC5014	103	88	0.5	4.7	4-M6
CC5016	110	88	0.5	5.5	4-M6
CC5018	120	95	0.6	7.5	4-M6
CC6018	142	106	1.0	17.6	4-M8
CC6022	166	116	1.2	28.8	4-M8
CC8018	187	130	2.0	61.0	4-M8
CC8022	222	147	3.0	131	4-M8
CC10020	258	160	4.6	268	4-M10
CC12018	280	190	5.3	367	4-M10
CC12022	334	207	8.1	806	4-M12

